

Fábrica de Tintas Isolaca, Lda.

Rua Narciso Machado, 12
Zona Industrial da Maia I, Sector X
4475-250 Maia (PT)
Telefone: + 351 22 943 87 50
Email: isolaca@isolaca.com

Technical Data Sheet

FTTP16300-8

Page 1 of 1

TP16300	PU CLEAR BASE COAT
---------	--------------------

CHARACTERISTICS:

Transparent base coat with excellent filling and transparency. It is particularly suitable for Mahogany or Walnut wood furniture. It is available with a range of hardeners that allow it to adapt to various applications.

TECHNICAL SUPPLY DATA:

Viscosity:..... 63±10 " FORD 4 (23°C)
Theoretical density:..... 0.985 Kg/L (23°C)

TECHNICAL APPLICATION DATA:

Application:.....	Airless/Airmix			
Mixing Ratio (Volume):.....	2:1			
Application Viscosity:.....	18-20	" FORD 4 (23°C)		
Component:.....	CP33641	CP34641	CP35641	CP36641
Solid content (mixture) (±1):.....	38.7%	39.5%	40.1%	41.3%
Dilution:.....	2-5%	2-5%	2.5-5.5%	8-11%
Drying Time:.....	3.5 h	3.5 h	3 h	2.5 h
Pot-Life:.....	2 h	2 h	1.5 h	1-1.5 h

To adjust the viscosity, our diluents should be used: DP2689, DP2695, DP94037.

The storage must be made with properly sealed containers and in cool places. The expiration date is 12 months.

The surfaces to be applied must be thoroughly cleaned and free from moisture.

This information gives a general idea of the main characteristics and application of the product, may therefore have to be adapted to the conditions in use of the product.

Our technical services are fully available for further clarification and suggestions.

Following a policy of continuous improvement, we reserve the right to change specifications without notice.

* value for guidance